

# HT1 Series

High Bay LED luminaires in a stylish troffer design for high ceiling applications requiring superior lumen output, ultra-long life and high quality of light

## Applications

- Automotive Showrooms
- Big Box Retailers
- Convention Centers
- Schools / Universities
- Warehouses



**Lumen Range**  
12,000 to 24,000 lm



**High Efficacy**  
up to 151LPW



**Ultra-Long Life**  
L70 at 278,000 hours

## Stylish Troffer Design

Clean and Harmonious Design

## Mounting Options

Suspended / Recessed

## Long Life

Up to L85 after 10 years (24/7)

## Dimming & Sensors

0-10V / IoT ready / Optional sensors

## Emergency Battery Backup

Optionally installed with 90 min. duration

## 5-year Warranty

10-year optional

## Product Offering



Nominal Lumens	Size	Lumen Output <sup>1</sup>	Efficacy	Watts	Max. Ambient Temp.	Part Number
12000	2x2	12207	133	92	45°C	HT10S-A1-12K-22-50-80-FR-LV-GRID-10V
12000	2x4	12207	133	92	45°C	HT10S-A1-12K-24-50-80-FR-LV-GRID-10V
18000	2x2	18133	138	131	45°C	HT10S-A1-18K-22-50-80-FR-LV-GRID-10V
18000	2x4	18538	151	123	45°C	HT10S-A1-18K-24-50-80-FR-LV-GRID-10V
24000	2x4	24112	129	187	45°C	HT10S-A1-24K-24-50-80-FR-LV-GRID-10V

<sup>1</sup>Typical at 277V (LV) and (25°C), 4000K/5000K, typical CRI 80+. 3500K multiplier is 0.93. Frosted Lens, +/-10%. No lens Lens multiplier is 1.08.

## Flex Lighting Solutions

(+1) 913-851-3000  
 lighting@flex.com  
 www.flexlightingsolutions.com

7320 W 162nd St.  
 Overland Park, KS  
 66085, USA

7825 Ridgepoint Dr.  
 Irving, TX  
 75063, USA

6201 America Center Dr.  
 San Jose, CA  
 95002, USA