

Linear Series 2.0

LED Linear Luminaires and Retrofit Linear Kits with ultra-long life, high uniformity and low glare with modular design for continuous-run lighting

Applications

- Parking Garages
- Warehouses
- Industrial Facilities
- Manufacturing
- Retail and Hospitality



Lumen Range
3,000 to 12,000 lm



High Efficacy
up to 151LPW



Ultra-Long Life
L70 at 309,000 hours



Universal Retrofit
multi-width 3.25" to 5.5"

Modular Design

4' sections linked by brackets

Mounting Options

Surface or suspended as stand-alone fixture
Retrofit kits utilize existing housing and wiring

Universal Retrofit

Adjustable width from 3.25" to 5.5"

Dimming & Sensors

0-10V. Optional motion/daylight sensors

Emergency Battery Backup

Optionally installed with 90 min. duration

5-year Warranty

10-year optional

Product Offering

Stand-alone Fixture **FXT**

Back Box included

Can be installed surface mounted or suspended (with hanger kit).

Retrofit Kit **RTR**

Back Box not included

Utilizes existing housing. Compatible with standard back boxes 4 $\frac{3}{8}$ " wide.

Retro Multi-Width Kit **RMW**

Bracket included

Back Box not included

Utilizes existing housing. Includes a bracket to adjust to any back box from 3.25" to 5.5" in width.

Nominal Lumens	Length	Lumen Output ¹	Efficacy	Watts	Max. Ambient Temp.	Part Number
3000	4'	3184	149	21	45°C	LR20S-A1-03K-04-40-80-FR
4000	4'	4552	140	33	45°C	LR20S-A1-04K-04-40-80-FR
6000	8'	6276	146	43	45°C	LR20S-A1-06K-08-40-80-FR
8000	8'	8186	148	55	45°C	LR20S-A1-08K-08-40-80-FR
9000	12'	9304	151	62	45°C	LR20S-A1-09K-12-40-80-FR
12000	12'	12278	130	94	45°C	LR20S-A1-12K-12-40-80-FR

¹Typical at 277V (LV) and (25°C), 4000K/5000K, typical CRI 80+. 3500K multiplier is 0.93. Frosted Lens, +/-10%. No lens Lens multiplier is 1.08.

Flex Lighting Solutions

North America
7320 W 162nd St.
Overland Park
KS 66085, USA

EMEA
Arthur-B.-Modine-Str. 1
70794 Filderstadt
Germany

Australia
359-361 City Rd
Southbank, VIC 3006
Australia

www.flexlightingsolutions.com · lighting.tech@flex.com · Phone: +1 (913) 851-3000