

LS1 Series

LED Linear Strip fixtures with a simplified linking system, saving money and time when creating continuous rows of lighting.

Applications

- Warehouses
- Industrial Facilities
- Manufacturing
- Parking Garages
- Retail



Lumen Range
3,000 to 5,000 lm



High Efficacy
up to 150 LPW



Ultra-Long Life
L70 at 309,000 hours



Linking System
saves money and time

Modular Design

4' linkable sections

Mounting Options

Surface or suspended as stand-alone fixture Retrofit kits utilize existing housing and wiring

Sensor Anywhere

Sensor can be placed anywhere along the run and operate all or part of the fixtures (LNK option)

Dimming, Sensors & Controls

0-10V. Optional motion/daylight sensors

Emergency Battery Backup

Optionally installed with 90 min. duration

5-year Warranty

10-year optional

Product Offering

Nominal Lumens	Lumen Output ¹	Efficacy	Watts	Part Number
3000	3704	150	25	LS10S-A1-03K-04-40-80-FR
4000	4835	145	33	LS10S-A1-04K-04-40-80-FR
5000	5898	140	42	LS10S-A1-05K-04-40-80-FR

¹Typical at 277V (LV) and (25°C), 4000K/5000K, Frosted Lens, +/-10%. Typical CRI 80+. 3500K multiplier is 0.93.

Flex Lighting Solutions

North America

7320 W 162nd St.
Overland Park
KS 66085, USA

EMEA

ul. Malinowska 28
83-100 Tczew
Poland

Australia

359-361 City Rd
Southbank, VIC 3006
Australia

www.flexlightingsolutions.com · lighting.tech@flex.com · Phone: +1 (913) 851-3000

All specifications subject to change without notice. Please see www.flexlightingsolutions.com for latest information. All values are typical or design values and series averages. Actual performance may differ as a result of end-user environments and applications. Consult Flex Lighting Solutions with specific inquiries. Copyright © 2018, Flex. All rights reserved. No part of this document may be reproduced in any form without the prior written permission of Flex.